

Agilent 1260 Infinity Thermostatted Column Compartment

Features, Specifications and Ordering Details



Convenient, stable column cooling and heating

The Agilent 1260 Infinity Thermostatted Column Compartment provides stable column cooling and heating up to 80 °C for standard applications. It fits neatly in a single stack of 1260 Infinity modules for lowest bench space requirements. An optional 2-position/6-port switching valve is available for 600 bar operation. For more sophisticated applications the Agilent 1290 Infinity Thermostatted Column Compartment is available, which fits seamlessly into any 1260 Infinity system.

Features

- Peltier cooling and heating for maximum temperature stability and application flexibility.
- Spacious column racks hold up to three full-length, 30 cm columns.
- Optional 2-position/6-port switching valve for 600 bar operation.
- Simultaneous column identification of two columns for faster operation and reduced laboratory costs.
- Independent heat exchangers with settable values facilitate two different temperature zones.
- Low internal volume contribution of just 9 µL for low dispersion.



Specifications – Agilent 1260 Infinity Thermostatted Column Compartment

Agilent 1260 Infinity Thermostatted Column Compartment		
Temperature range	10 degrees below ambient to 80 °C	
Temperature stability	± 0.15 °C	
Temperature accuracy	\pm 0.8 °C with calibration \pm 0.5 °C	
Column capacity	Three 30 cm columns	
Heat-up/cool-down time	5 min from ambient to 40 °C 10 min from 40 °C to 20 °C	
Internal volume	3 μL left heat exchanger 6 μL right heat exchanger	
GLP	Column identification module for GLP documentation of column type	

Ordering Details – Agilent 1260 Infinity Thermostatted Column Compartment

Description	Product Number
Agilent 1260 Infinity Thermostatted Column Compartment	G1316A
2-position/6-port column switching valve for 600 bar operation with 0.17 mm id connection capillaries	G1316A#055

www.agilent.com/chem/1200

© Agilent Technologies, Inc., 2010 Published in USA, July 1, 2010 Publication Number 5990-6125EN

